



enerflex.

raising the standards



POWER SUPPLIES



1202SM-1



1202SM-1



SPECIFICATION

- Full current to load
- 12-14VDC adjustable voltage output
- Additional battery charging
- Deep discharge protection
- Current limiting
- Short circuit protection
- 230V fused input
- Mains transient protection
- Compliant to EMC EN61000-6-1 & 3
- **Up to 92% energy efficiency (reduced running costs and lower power usage)**

Available in the following models as standard:
1201SM-1 / 1201SM-2 / 1202SM-1 / 1202SM-2
1203SM-1 / 1203SM-2 / 1205SM-1 / 1205SM-2
12TENS-2

DIMENSIONS

SM-1
• 225H x 196W x 75D (mm)
• 1.46kg (Boxed) • 1.32kg (Unboxed)

SM-2
• 310H x 340W x 80D (mm)
• 3.07Kg Boxed • 2.84Kg Unboxed

FEATURES

- Switchmode technology
- Din rail design for greater versatility
- Mild steel construction
- White powder coated
- LED Indicators (mains, batt, output)
- Seperate fused main connectors
- Full electronic protection
- Onboard tamper protection
- Converts power more efficiently
- Multiple cable entry
- Allows for 1 x 7/9aH batteries (SM-1)

Utilising market leading Gallium Nitride technology (GaN)

CONTENTS

- Power Supply Unit
- 2 x Battery Leads (1 x Red, 1 x Black)
- 1 x Earth Lead - Connected
- Wiring instructions included

OTHER PRODUCTS

IPBOX-2



VP-EEB



TLI-45



CDL-300

