



STAINLESS PIEZO BUTTON

EXIT BUTTONS

Market leading exit buttons, that is both hard wearing and cost effective. Suitable for use in applications up to 30V.



K-PIL-GS/PTE



K-PIL-BS/PFA



K-PIL-RS/EPTE

SPECIFICATION

- K-PIL-__
- Contacts: NO/COM
 - Input current: 500mA @24V AC/DC
 - Contact resistance: <50mΩ
 - Voltage: 12-24VDC
 - Wear resistant legend
 - Security screws (allen key type)
 - Internal or External use
 - Button is rated at IP68
 - Operating temperature: -40C to +70C

FEATURES

- K-PIL-__
- Stainless steel piezo button
 - Momentary operation
 - LED status:
 - Red / Green / Blue or Yellow (Static)
 - No moving parts
 - Flush fitting as standard
 - Fits on standard RGL Surface Boxes
 - Ideal for general/sensitive areas
 - Distance between fixing holes 60mm

The product can be made up with various different plates within the RGL range.

OTHER PRODUCTS

WP66-G-ILG/GR



TLI45



SPX-26M



CDL-300



DIMENSIONS

- K-PIL-__
- 85H x 85W x 28D (mm)
 - 300g (Boxed)
 - 260g (Unboxed)

CONTENTS

- K-PIL-__
- Illuminated Piezo Switch
 - Stainless Steel Plate (2mm)
 - 2 Security Screws
 - Allen Key
 - Electrical Back Box



Manufactured by a BSIA Member