



PROXIMITY READER

KEYPAD RANGE

Market leading keypads and door entry accessories, as well as complete door access control solutions.



RD26-C

Compatible with the following products



KPX2000



PX2000



KP-HD-CARD



KP-FOB

SPECIFICATION

RD26-C

- High impact plastic reader for external use
- Fully encapsulated to IP65
- 9-12VDC @ max 50mA
- 26 bit EM formatted reader
- Wiegand 4 wire connections
- Card read time of 120mS
- Operating frequency 125kHz
- Maximum transfer distance of 100m (screened cable)
- Operating temperature -10° to +60°

FEATURES

RD26-C

- Small compact design
- LED indication
- Weather resistant
- Simple wiring to controller
- Encapsulated electronics
- Choice of cards or fobs
- Compatible with Wiegand type controllers
- To work with the RGL KPX2000

Suitable Accessories

- KP-FOB-BE
- KP-FOB-GY
- KP-CARD
- KP-HD-CARD

OTHER PRODUCTS

IEPS/PTE



120ISM-1



ML600



DU-NT/TF



DIMENSIONS

RD26-C

- 78x42x12 (mm) (HxWxD)
- 86g (Boxed)
- 58g (Unboxed)

CONTENTS

RD26-C



Manufactured by a BSIA Member