



WEATHERPROOF EXIT BUTTON

EXIT BUTTONS

Market leading illuminated button, that is both hard wearing and cost effective. Suitable for use in applications up to 30V.



WP66-G-ILG/PTO



WP66-G-ILG/GR



WP66-Y-ILB/PFA

SPECIFICATION

- WP66
- Contacts: NO/COM
 - Contact rating: 500mA @24V AC/DC
 - Voltage: 12-24VDC
 - Wear resistant legend (others available on request)
 - Button is rated at IP68
 - IP66 ingress protection (enclosure)
 - Robust two part cross polymer housing
 - M16/20 pre moulded conduit knockouts
 - Silver contacts
 - Operating temperature -20° to +60°C
 - Operating travel: 2mm
 - Contact resistance: <50mΩ
 - Operating life (mechanical): 1,000,000

DIMENSIONS

- WP66
- 85H x 90W x 60/80D (mm)
 - 248g (Boxed)
 - 200g (Unboxed)

FEATURES

- WP66
- LED status:
 - Red / Green / Blue or Yellow (Static)
 - Momentary operation / contact
 - High impact plastic back box
 - Surface fitting
 - Easy clean surface.
 - IP66 weatherproof unit

Any variations of the above switches are available.

Alternative Legends Available:
PRESS TO EXIT (Green)
DOOR RELEASE (Green)
EMERGENCY STOP (Red)
PANIC ALARM (Red)
POOL ALARM (Blue)

CONTENTS

- WP66
- Red / Green / Blue or Yellow Illuminated Switch
 - 4 Screws
 - Surface Enclosure

OTHER PRODUCTS

WP-EBSS25



K-RB/FAS



WP66-Y-KR/ES



DU-GB/PTE



Manufactured by a BSIA Member