



WEATHERPROOF EXIT BUTTON

EXIT BUTTONS

Market leading stainless steel button, that is both hard wearing and cost effective. Suitable for use in applications up to 30V.



WP66-G-SS/PTE

SPECIFICATION

WP66-G-SS/PTE

- Contacts: Double pole N/O - N/C
- Output: 4 AMP contact @ 30V AC/DC
- Wear resistant legend (others available on request)
- External use
- Button rated at IP65
- Enclosure rated at IP66
- Robust two part cross polymer housing
- M16/20 pre moulded conduit knockouts
- Silver contacts
- Operating temperature -20° to +60°C
- Operating travel: 2mm
- Contact resistance: 10m OHM (Max)
- Operating life (mechanical): 1,000,000

FEATURES

WP66-G-SS/PTE

- Stainless Steel Button
- Momentary operation / contact
- High impact plastic back box
- Surface fitting
- Easy clean surface
- Ideal for general / sensitive areas
- IP66 weatherproof unit

Alternative Legends Available:

- PUSH TO OPEN
- GATE RELEASE
- DOOR RELEASE

OTHER PRODUCTS

EBNT/TF-IPLUS



AH600



ML600



JMB/KS-1



DIMENSIONS

WP66-G-SS/PTE

- 85H x 90W x 60/80D (mm)
- 248g (Boxed)
- 200g (Unboxed)

CONTENTS

WP66-G-SS/PTE

- Stainless Steel Exit Button
- 4 Screws
- Surface Enclosure



Manufactured by a BSIA Member