



WEATHERPROOF EXIT BUTTON

EXIT BUTTONS

Market leading door release button, that is both hard wearing and cost effective. Suitable for use in applications up to 30V.



WP66-Y-TTO/ES



WP66-Y-TTO



WP66-Y-KR/ES

SPECIFICATION

WP66

- Contacts: Double pole N/O - N/C
- Output: 3 AMP contact @ 240V AC (2AMP @12/24VDC)
- Wear resistant legend (others available on request)
- External use
- IP66 ingress protection (button & enclosure)
- Robust two part cross polymer housing
- M16/20 pre moulded conduit knockouts
- Operating temperature -20° to +60°c

FEATURES

WP66

- Momentary operation / contact
- High impact plastic back box
- Surface fitting
- Easy clean surface.
- Ideal for general/sensitive areas
- IP66 weatherproof unit

Any variations of the above switches are available, including switching to a grey back box.

OTHER PRODUCTS

EXML600-GATE



WP66-Y-ILB/PFA



K-PIL-BS/PFA



DU-GB/PTE



DIMENSIONS

WP66

- 85H x 90W x 60/80D (mm)
- 248g (Boxed)
- 200g (Unboxed)

CONTENTS

WP66

- Red Latching Button
- 4 Screws
- Surface Enclosure
- (2 x Keys with KR version)



Manufactured by a BSIA Member