Weatherproof Touch Free Exit Device

EXIT BUTTONS

Market leading request to exit buttons, that are both hard wearing and cost effective. Suitable for use in applications where contactless options are a priority.



WP-TF-1

SPECIFICATION

WP-TF-1
- Contacts: Double pole NONC contacts
- Contact Load: 0.5A @ AC 120V / 1A @ DC24V
- Dual voltage 12/24 VDC @ 45mA operating
- +/- 10% voltage tolerance
- Etched legend (various options available)
- Security screws (allen key type)
- Button rated IP65 ingress protection
- Adjustable relay opening times (0.5 to 20 sec)
- Adjustable proximity distance (3 to 12 cm)
- -10° to +70° operating temperature
- Designed to prevent interference with other infra red devices
- Rated IP66 ingress protection

Requires a permanent power supply
- volt free contacts

FEATURES

WP-TF-1
- 38mm Touch free sensor button
- Illumination - Green to red (or red to green)
- High impact plastic back box
- Can be surface or flush fitting
- Easy clean surface
- Ideal for general / sensitive areas
- Screw footprint for flush fitting onto standard back box
- Distance between fixing holes 60mm
- Gasket and gland included

Suitable Alternative Back Boxes
- EXTR02 (Aluminium Extrusion 40mm)
- SSBB02 (Stainless Steel Back Box 42mm)
- PBB05 (Green or Black Back Box 40mm)

DIMENSIONS

WP-TF-1
- 85H x 85W x 40/50D (mm)
- 238g (Boxed)
- 202g (Unboxed)

CONTENTS

WP-TF-1
- Touch free button on SS Plate
- Back box
- Wires & connector
- Screw bag
- Gland
- Gasket
- Instructions

OTHER PRODUCTS

1201SM-1



RD26-C



ML600



DU-NT/TF

