



Product Image



Part number

909020116 – PAC OneProx™ GS3 LF Vandal Reader - yellow and black
909022116 – PAC OneProx™ GS3 LF Vandal Reader - blue and grey

Dimensions

W 100 x H 100 x D 16mm

Weight

410g

RFid Frequency

Low Frequency (125kHz and 153.6kHz)

PAC ID Devices

PAC, Stanley, KeyPAC, Wiegand

Programmable Output Formats

PAC, PAC64 and Wiegand

Maximum Read Range

40mm

Intruder Grading

Security Grade 3

Environment

IP65 - Indoor/ Outdoor weather resistant

Power

12 – 24V DC, <100mA @ 12V DC

Operating Temperature

-40 to 66 oC

Operating Humidity

10 to 85% Relative Humidity

Audio/Visual Indicators

Audible Sounder and Red/Green LEDs

Tamper Output

Yes, certified to EN 50131-1 and EN 50131-3

Recommended Cabling

PAC output - 6 core 24 AWG alarm cable (unscreened)
Wiegand output – 5 core 22 AWG cable

Material

Stainless Steel & Polycarbonate

Certification

CE compliant



Date of print/release: (September 2020)

This document is provided by STANLEY Security or its affiliates ("STANLEY") for general information purposes only. STANLEY warrant the accuracy of the data as at the date of print/release, but it may be subject to change after such date. STANLEY will not be responsible for any loss or damage that may arise from reliance thereof. Copyright © STANLEY Security 2020. PAC, GDX and 3xLOGIC are the trade marks of STANLEY Security, Stanley Black & Decker, Inc., or their affiliates.

Ordering Information:

PAC Access Control, 1 Park Gate Close,
Bredbury, Stockport, Cheshire, SK6 2SZ
customerservices@pacgdx.com | +44 (0) 161 406 3400
www.pacgdx.com