



Product Image		
Part Number	909030055 –PAC 512 DC Access Controller - DIN Mount 909030765 – PAC 512 DC Access Controller - PCB only	909030054 –Boxed PAC 512 DC Access Controller with 3 Amp PSU 909031074 – Boxed PAC 512 DC Access Controller in a Sarel Cabinet with 3 Amp PSU 909031076 - Boxed PAC 512 DC Access Controller in a Sarel Cabinet with 3 Amp PSU, GSM Modem Kit and Low Profile Aerial
Dimensions	W 181 x H 65 x D 125mm	Boxed - W 335 x H 335 x D 90mm
Operating Temperature	0°C to +35°C	
Operating Humidity	10% to 85% Relative Humidity	
Number of ID Devices supported	20,000	
Supported access control reader protocol	PAC PAC64 Wiegand	
Supported ID Device formats	PAC (Cards and Tokens) Key PAC (Cards and Tokens) Stanley (Tokens) PAC Ops™ Lite (Cards and Tokens) PAC Ops™ (Cards and Tokens)	
Number of doors supported	2 doors with up to 4 access control devices as per the following options: • An access control reader per door • An access control reader and Push To Exit (PTE) device per door • 2 access control readers per door (read-in and read-out)	
Configuration	via PC with PAC Access Central or Easinet software	
Event storage	20,000 events	



Access Controller input devices	PAC readers (LF, HF, MT, Architect and Biometric) PAC PTE devices Door contacts Alarm inputs
Input connection features	1 x tamper alarm input 1 x override input 1 x RS-232 input 1 x RS-485 input
Output connection features	2 x 5 Amp relays @ 30V DC
Distance to input devices	70m
Recommended Cabling	0.22mm 8 core alarm cable
Power input	10.5 – 28 V DC 50/60 Hz @ 350mA
Warranty	5 years against electronic failure
Standards Compliance	CE, RoHS & WEEE compliant
Boxed Product Contents	Installation guide